



Technical Data



TYPES	Capacity		Cutting Length	Rake Angle	Main Motor	Working Pressure	Number of Hold-downs	Strokes per Minute	Capacity of Oil Tank	Back-gauge Range	Back-gauge Motor	Approx. Weight
	≤450 N/mm ²	≤700 N/mm ²										
	mm	mm										
HNC 3106	6	4	3070	0.5°-1.5°	11	260	16	20-32	240	1000	0.37	7800
HNC 3110	10	6	3070	0.5°-2.0°	22	260	15	12-18	360	1000	0.37	11000
HNC 3113	13	8	3070	0.5°-2.5°	30	260	15	9-14	360	1000	0.37	13000
HNC 3116	16	10	3070	0.5°-3.0°	30	260	15	8-14	400	1000	0.55	16500
HNC 3120	20	13	3070	0.5°-3.0°	37	260	16	6-10	400	1000	0.55	21000
HNC 3125	25	16	3070	0.5°-3.5°	45	260	15	4-6	600	1000	0.55	23000
HNC 4106	6	4	4070	0.5°-1.5°	11	260	21	16-25	360	1000	0.55	12000
HNC 4110	10	6	4070	0.5°-2.0°	22	260	21	9-14	360	1000	0.55	15000
HNC 4113	13	8	4070	0.5°-2.5°	30	260	21	7-14	400	1000	0.55	18000
HNC 4116	16	10	4070	0.5°-3.0°	30	260	21	7-12	400	1000	0.55	23500
HNC 4120	20	13	4070	0.5°-3.0°	37	260	21	6-9	400	1000	0.55	26000
HNC 6106	6	4	6070	0.5°-2.0°	18.5	260	30	12-18	360	1000	0.55	22000
HNC 6110	10	6	6070	0.5°-2.0°	22	260	30	6-10	400	1000	0.55	30000
HNC 6113	13	8	6070	0.5°-2.5°	30	260	30	6-10	400	1000	0.75	38000
HNC 6116	16	10	6070	0.5°-3.0°	37	260	30	5-9	400	1000	0.75	43000
HNC 6120	20	13	6070	0.5°-3.0°	37	260	30	5-9	600	1000	0.75	48000



Machines built with CE-safety conformity are available as option.
Design and specifications are subject to change without notice.